



**NOTCH**  
Manufacturing, Inc.



## SLURRY BUCKETS



### SLURRY BUCKET - SB24/SB30

**SB24 SIZES:** 60", 66", 72", 78", 84", 90", & 96"

**SB30 SIZES:** 72", 78", 84", 90", 96", & 102"

**SMALL MODEL BUCKET DIMENSIONS:** 24½" HIGH X 39½" DEEP, RECOMMENDED FOR LOADERS WITH OPERATING CAPACITY OF 3,000 LBS. OR LESS, CONSTRUCTED OF 3/16" HIGH TENSILE STEEL

**LARGE MODEL BUCKET DIMENSIONS:** 30" HIGH X 48½" DEEP, RECOMMENDED FOR LOADERS

WITH OPERATING CAPACITY OF 4,000 LBS. OR LESS, CONSTRUCTED OF ¼" HIGH TENSILE STEEL

ROLLED TOP DESIGN, NO SHARP CORNERS FOR SAFE WORK ENVIRONMENT

¾" X 6" CUTTING EDGE WITH HOLES TO ACCEPT BOLT ON CUTTING EDGE

UNIVERSAL AND EURO ATTACHMENTS STANDARD, OTHER ATTACHMENTS AVAILABLE



### OPTIONAL FORGED TEETH

AVAILABLE ON ANY BUCKET

TOOTH HOLDER IS WELDED ON TO BUCKET'S EDGE, REPLACEABLE TOOTH IS PINNED ON WITH A ROLL PIN

## FORAGE GRAPPLE BUCKET



### FORAGE GRAPPLE BUCKET - FGB

**SIZES:** 60", 66", 72", 78", 84", 90", 96" & 102"

RECOMMENDED FOR LOADERS WITH OPERATING CAPACITY OF 4,000 LBS OR LESS

**BUCKET DIMENSIONS:** 23½" HIGH X 38" DEEP

CONSTRUCTED OF ¼" HIGH TENSILE STEEL

ROLLED TOP DESIGN, NO SHARP CORNERS FOR SAFE WORK ENVIRONMENT

HIGH SIDES AND ENCLOSED GRAPPLE FOR HANDLING LOOSE FORAGE

¾" X 6" CUTTING EDGE WITH HOLES TO ACCEPT BOLT ON CUTTING EDGE

TWIN HYDRAULIC CYLINDERS WITH CASTED GREASABLE ENDS, HEAT TREATED FOR STRENGTH AND WEARABILITY, CYLINDER COVERS PROTECT CYLINDER AND HOSES

1¼" PIVOT PINS WITH BUSHINGS, GREASABLE AT ALL PIVOT POINTS

UNIVERSAL AND EURO ATTACHMENTS STANDARD, OTHER ATTACHMENTS AVAILABLE



Notch Manufacturing reserves the right to change its products or their specifications at any time without notice or obligation.

**Notch Manufacturing Inc.**

23664 State Hwy. 4 • Lake Henry, MN 56362 • 320-243-7248 • Fax: 320-243-7245 • www.notchmfginc.com