



## LOW PROFILE BUCKETS



### LOW PROFILE BUCKET - LP3K/LP4K

SIZES: 60", 66", 72", 78", 84", 90", 96" & 102"

**3K MODEL** RECOMMENDED FOR LOADERS WITH OPERATING CAPACITY

OF 3000 LBS. OR LESS

**4K MODEL** RECOMMENDED FOR LOADERS WITH OPERATING CAPACITY OF 4000 LBS. OR LESS

BUCKET DIMENSIONS: 21" HIGH X 36" DEEP

CONSTRUCTED WITH HIGH TENSILE STEEL: 3K BUCKET 3/16", 4K BUCKET 1/4"

ROLLED TOP DESIGN, NO SHARP CORNERS FOR SAFE WORK ENVIRONMENT

3/4" X 6" CUTTING EDGE WITH HOLES TO ACCEPT BOLT ON CUTTING EDGE

UNIVERSAL AND EURO ATTACHMENTS STANDARD, OTHER ATTACHMENTS AVAILABLE



### OPTIONAL FORGED TEETH

AVAILABLE ON ANY BUCKET

TOOTH HOLDER IS WELDED ON TO BUCKET'S EDGE, REPLACEABLE TOOTH IS PINNED ON WITH A ROLL PIN



### HIGH BACK GRAPPLE LOW PROFILE UTILITY BUCKET - LPUHG

LOW PROFILE UTILITY BUCKET 4K BASE UNIT WITH HIGH BACK SINGLE GRAPPLE

SIZES: 72", 78", 84", 90" 96" & 102"

BUCKET DIMENSIONS: 23 1/2" HIGH X 42" DEEP

72" GRAPPLE OPENING

USED TO MOVE 6' ROUND BALES



### LOW PROFILE UTILITY BUCKET - LPU3K/LPU4K

SIZES: 60", 66", 72", 78", 84", 90", 96" & 102"

CONSTRUCTED LIKE THE LOW PROFILE BUCKETS

BUCKET DIMENSIONS: 23 1/2" HIGH X 38", 42", OR 48" DEEP (48" DEEP ONLY OFFERED IN 4K)



### GRAPPLE LOW PROFILE UTILITY BUCKET - LPUG4K

LOW PROFILE UTILITY BUCKET 4K BASE UNIT WITH SINGLE GRAPPLE

BUCKET DIMENSIONS:

23 1/2" HIGH X 38" OR 42" DEEP

56" GRAPPLE OPENING

TWIN 2" HYDRAULIC CYLINDERS WITH CASTED GREASABLE ENDS

HEAT TREATED CYLINDER PINS FOR STRENGTH AND WEARABILITY

CYLINDER COVERS PROTECT CYLINDER AND HOSES

1 1/4" PIVOT PINS WITH BUSHINGS, GREASABLE AT ALL PIVOT POINTS

3/4" X 6" CUTTING EDGE WITH HOLES TO ACCEPT BOLT ON CUTTING EDGE

LOW SIDES STANDARD, ALSO AVAILABLE WITH FULL SIDES (PICTURED) OR BOLT ON SIDES



### DUAL GRAPPLE LOW PROFILE UTILITY BUCKET - LPUDG4K

UNIT JUST LIKE SINGLE GRAPPLE, BUT WITH INDEPENDENT DUAL GRAPPLES FOR BETTER MANAGEMENT OF UNEVEN MATERIALS