



NOTCH

Manufacturing, Inc.



MATERIAL BUCKETS



MATERIAL BUCKET - MB3K/MB4K

SIZES: 72", 78", 84", 90", 96", 102", 108", & 120"

3K MODEL RECOMMENDED FOR LOADERS WITH OPERATING CAPACITY OF 3000 LBS. OR LESS, CONSTRUCTED WITH 10 GAUGE ALLOY STEEL

4K MODEL RECOMMENDED FOR LOADERS WITH OPERATING CAPACITY OF 4000 LBS. OR LESS, CONSTRUCTED WITH 3/16" HIGH TENSILE STEEL

BUCKET DIMENSIONS: 30" HIGH X 42" DEEP

ROLLED TOP DESIGN, NO SHARP CORNERS FOR A SAFE WORK ENVIRONMENT

3/4" X 6" CUTTING EDGE WITH HOLES TO ACCEPT BOLT ON CUTTING EDGE

UNIVERSAL AND EURO ATTACHMENTS STANDARD, OTHER ATTACHMENTS AVAILABLE



OPTIONAL FORGED TEETH

AVAILABLE ON ANY BUCKET

TOOTH HOLDER IS WELDED ON TO BUCKET'S EDGE, REPLACEABLE TOOTH IS PINNED ON WITH A ROLL PIN

HIGH BACK GRAPPLE MATERIAL BUCKET MBHG4K

MATERIAL BUCKET 4K BASE UNIT WITH HIGH BACK SINGLE GRAPPLE CLAW

71" GRAPPLE OPENING

(NOT PICTURED)

GRAPPLE MATERIAL BUCKET MBG4K

MATERIAL BUCKET 4K BASE

UNIT WITH SINGLE GRAPPLE CLAW

59" GRAPPLE OPENING

TWIN 2½" HYDRAULIC CYLINDERS WITH CASTED GREASABLE ENDS

HEAT TREATED CYLINDER PINS FOR STRENGTH AND WEARABILITY

CYLINDER COVERS PROTECT CYLINDER AND HOSES

1¾" PIVOT PINS WITH BUSHINGS, GREASABLE AT ALL PIVOT POINTS

LOW SIDES STANDARD, ALSO AVAILABLE WITH HIGH SIDES OR BOLT ON HIGH SIDES

DUAL GRAPPLE MATERIAL BUCKET MBDG4K

MATERIAL BUCKET 4K BASE UNIT WITH DUAL GRAPPLES FOR BETTER HANDLING OF UNEVEN MATERIAL

59" GRAPPLE OPENING

TWIN 2½" HYDRAULIC CYLINDERS WITH CASTED GREASABLE ENDS

HEAT TREATED CYLINDER PINS FOR STRENGTH AND WEARABILITY

CYLINDER COVERS PROTECT CYLINDER AND HOSES

1¾" PIVOT PINS WITH BUSHINGS, GREASABLE AT ALL PIVOT POINTS

(NOT PICTURED)

Notch Manufacturing reserves the right to change its products or their specifications at any time without notice or obligation.

Notch Manufacturing Inc.

23664 State Hwy. 4 • Lake Henry, MN 56362 • 320-243-7248 • Fax: 320-243-7245 • www.notchmfginc.com